

GAS DETECTOR

AC Single Type DC Single Type

TMETCO.VN

- | **Model** | SHT-201(AC Type), SHT-202(DC Type)
- | **Type** | 12V.DC, Single type, Waterproof, Diffusion type, Catalytic combustion cell type, Immediately Alarm type
- | **Measuring gases** | LNG, LPG
- | **Operating power** | 220/110V.AC(AC Type), 12V.DC(DC Type)
- | **Measuring range** | 0~100%(LEL)
- | **Alarm setting** | 20%(LEL)
- | **Alarm density** | LNG(0.06~1.25%)/LPG(0.06~0.45%)
- | **Alarm method** | Buzzer sound - Automatic reset, Alarm of flickering/Leakage LED - Yellow flickering
- | **Cable color** | 12V.DC(White-plus), 0V(Black-minus) - AC Type
12V.DC(Red-plus), 0V(Black-minus), 12V.DC(White-Signal) - DC Type
- | **Signal output** | 12V.DC(White-plus, Black-minus)
- | **Alarm display** | Power(LED green-on), Alarm(LED yellow flickering)
- | **Power consumption** | Normal(2W) / Alarm(2.1W)
- | **Safety** | Over current off, Overheating prevent logic
- | **Alarm sound** | Over 70dB
- | **Fuse** | 0.3A(300mA)
- | **Usable area** | 17m²
- | **Alarm density point** | LEL(%) below(1/4)
- | **Operating Temp'/Humi'** | -20°C~+40°C/below 85%RH
- | **Applications Use** | Apartment, Office building, Multi-family homes, Condominiums, Home automation facilities, etc.
- | **Weight** | 0.15Kgs



DIMENSION (mm)

